

Protek 1000

Single Wire V-Mesh Clip Fence System

The Protek 1000 mesh fence system provides a perimeter security fence that is aesthetically pleasing with high through-visibility, helping it to blend into its surroundings.

Protek 1000 features welded single-wire mesh panels with horizontal triangular folds that help to form a strong, rigid fence line. Adjoining panels are held together with metal clips that are then pinned into posts using pre-drilled holes. It is particularly suitable for use as a general purpose boundary fence for schools, public areas and retail parks.

Applications

- Schools and Colleges
- Public Places & Buildings
- Retail Parks
- Business Parks





Other RAL colours available

Specification

Nominal	Panel Size	Post Centres (mm)	No. 'V'Bars per Panel	Overall Length of Post (mm)	Post Size (mm)	Number of Clips	
Fence Height (m)	Height x Width (mm)					Per Post	Per Corner
1.2	1,230 x 3,005	3,030	2	1,800	60 x 60	3	6
1.8	1,730 x 3,005	3,030	3	2,400	60 x 60	4	8
2.0	1,930 x 3,005	3,030	3	2,600	60 x 60	4	8
2.4	2,330 x 3,005	3,030	3	3,100	60 x 60	5	10
3.0	2,930 x 2,455	2,480	4	3,750	60 x 60	6	12

Data subject to change



Harrow Fencing Supplies Ltd, 79/89 Greenford Road, Harrow, Middx. HA1 3QF www.harrowfencing.com | 020 8138 0245

Protek 1000

DATASHEET

Version 1.4 | 04-24



Posts, Clips and Fixings

The posts and clips that are offered provide a fixing system which secures the panels but allows for variations. The system is easy to install and allows the panels to be stepped, helping the fence line to follow the contours of the ground. With the vandal resistant security fixings this post and clip system provides a reasonable level of security to any boundary.

Please note: Posts feature extra stepping holes to allow the fence line to be stepped on sloping ground. When not used, these holes do not require a security screw or clip.

Intermediate post



Internal corner post



End post



External corner post



Harrow Fencing Supplies Ltd, 79/89 Greenford Road, Harrow, Middx. HA1 3QF

www.harrowfencing.com | 020 8138 0245

Protek is a registered trademark of Alexandra Security Ltd

While care has been taken to ensure that all information provided on this data sheet is accurate, we reserve the right to change product specifications at any time. E&OE.

Product Technical Information

Panels:

- Mesh size 200 x 50mm 5mm horizontal wire / 4mm vertical wire (conforms to BS 1722-14:2017).
- Triangular Folds: 2, 3 or 4 per panel (height dependant).
- Panels can be inverted to create flat top option.
- Manufactured to BS 4102 and galvanised to BS EN 10244-2:2001 class D.
- Weld strength is 75% of the minimum tensile strength of the wire (tensile range 540-690 N/m2).

Posts:

- Dig-in posts. Post size: 60 x 60mm SHS.
- Post material manufactured to BS EN 10210-2:1997 and galvanised to BS EN 10346:2009.
- Supplied with 60 x 60mm plastic hooked cap.
- Post feature 2 extra holes for stepping (unfilled).

Fixings:

- Durable metal clips.
- M8 x 30 stainless steel security screw.
- M8 shear nut with M8 washer.

Finishings:

- Panels & Posts are galvanised before being powder coated to BS EN 13438:2005 (min 100 micron).
- Standard colours are RAL 6005 (Moss Green) and RAL 9005 (Black).
- Other RAL colours available as special order, including marine grade coating.

Post Options:

- Cranked posts (internal and external / top and bottom).
- Face fix (for flush against walls).
- Base-plated (flush to front, back or centrally) available as special order for installation onto concrete and other hard surfaces.

15 Year Product Guarantee



We work hard to ensure that when you choose us, there are no shocks or surprises, and that the finished item we deliver looks and functions every bit as well as the initial concept. In addition, we are able to offer a 15-year guarantee, covering the performance and appearance of our mesh fencing systems. Giving you added confidence when specifying our products.

